

U4/52 Vinnicombe Drive

# Safety Data Sheet

Page 1 of 5

# Section 1 - Identification of The Material and Supplier

Sealants Australasia Pty Ltd Phone: 08 9456 3627 (business hours)

Fax: 08 9456 3927

Canning Vale, WA 6155 AUSTRALIA

Chemical nature: Sealants

Trade Name: SA CONTRACTORS SILICONE

Product Use: Silicone Elastomer

Creation Date: July, 2016

This version issued: August, 2016 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 1126 from anywhere in Australia

# **Section 2 - Hazards Identification**

## **Statement of Hazardous Nature**

This product is classified as: Xi, Irritating. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA or IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good according to Australian Dangerous Goods (ADG)

Code, IATA or IMDG/IMSBC criteria. **UN Number:** None allocated



# **GHS Signal word: WARNING**

Skin Corrosion /Irritation Category 2

#### **HAZARD STATEMENT:**

H315: Causes skin irritation.

#### **PREVENTION**

P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves, protective clothing and eye or face protection.

#### **RESPONSE**

P313: Get medical advice/attention.

P332: If skin irritation occurs: wash thoroughly with soap and water.

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

#### **STORAGE**

P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

### **DISPOSAL**

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

# **Emergency Overview**

Physical Description & Colour: Clear Paste

Odour: Acetic Acid

Issued by: Sealants Australasia Pty Ltd
Page 1 of 5
Phone 08 9456 3627 (Business Hours)
Product: SA CONTRACTORS SILICONE
This version issued: August, 2016



Page 2 of 5

Major Health Hazards: Causes skin irritation.

## Section 3 - Composition/Information on Ingredients

| Ingredients                                | CAS No     | Conc,%  | TWA (mg/m <sup>3</sup> ) | STEL (mg/m <sup>3</sup> ) |
|--|------------|---------|--------------------------|---------------------------|
| Amorphous silica                           | 7631-86-9  | 1-10    | 2                        | not set                   |
| Methyltriacetoxysilane                     | 4253-34-3  | 1-10    | not set                  | not set                   |
| Polyethylene glycol                        | 25322-68-3 | 0.1-1.0 | not set                  | not set                   |
| Acetic acid                                | 64-19-7    | 0.1-1.0 | 25                       | 37                        |
| Octamethylcyclotetrasiloxane               | 556-67-2   | 0.1-1.0 | not set                  | not set                   |
| Other ingredients said to be non hazardous | secret     | to 100  | not set                  | not set                   |

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## **Section 4 - First Aid Measures**

### **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** If irritation is experienced, remove victim from area and allow to breath fresh air. If irritation persists, call a doctor or poisons information centre.

**Skin Contact:** Quickly and gently brush away excess particles. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** Quickly and gently brush particles from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

## **Section 5 - Fire Fighting Measures**

**Fire and Explosion Hazards**: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

**Fire Fighting:** When fighting fires involving significant quantities of this product, no special equipment is believed to be necessary.

Flash point: >94°C
Upper Flammability Limit: No data.
Lower Flammability Limit: No data.
Autoignition temperature: No data.

Flammability Class: Combustible solid.

Issued by: Sealants Australasia Pty Ltd Product: SA CONTRACTORS SILICONE

Page 2 of 5

Phone 08 9456 3627 (Business Hours) This version issued: August, 2016



Page 3 of 5

## **Section 6 - Accidental Release Measures**

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

# Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers of this product in a well ventilated area. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further storage instructions on the label.

## **Section 8 - Exposure Controls and Personal Protection**

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

| SWA Exposure Limits | TWA (mg/m³) | STEL (mg/m³) |
|---------------------|-------------|--------------|
| Amorphous silica    | 2           | not set      |
| Acetic acid         | 25          | 37           |

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** There is no data that enables us to recommend any type except that it should be impermeable.

**Respirator:** If there is a significant chance that dusts are likely to build up in the area where this product is being used, we recommend that you use a suitable dust mask. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

# **Section 9 - Physical and Chemical Properties:**

Physical Description & colour: Clear Paste
Odour: Acetic Acid
Boiling Point: Not available.

**Freezing/Melting Point:** No specific data. Solid at normal temperatures.

Volatiles:
Vapour Pressure:
Vapour Density:
Specific Gravity:
Water Solubility:
PH:
No data.
Not applicable.
No data.
Insoluble.
No data.

Issued by: Sealants Australasia Pty Ltd
Page 3 of 5
Phone 08 9456 3627 (Business Hours)
Product: SA CONTRACTORS SILICONE
This version issued: August, 2016



Page 4 of 5

Volatility:No data.Odour Threshold:No data.Evaporation Rate:Not applicable.

Coeff Oil/water Distribution: No data

Viscosity: Not applicable. Autoignition temp: No data.

# Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated.

**Incompatibilities:** No particular Incompatibilities.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Silica and other silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: Polymerisation reactions are unlikely; they are not expected to occur.

## **Section 11 - Toxicological Information**

**Local Effects:** 

**Target Organs:** There is no data to hand indicating any particular target organs.

### **Classification of Hazardous Ingredients**

Ingredient Risk Phrases

Acetic Acid No risk phrases at concentrations found in this product

Flammable liquid - category 3

Skin corrosion - category 1A

Octamethylcyclotetrasiloxane No risk phrases at concentrations found in this product

Reproductive toxicity - category 2

Hazardous to the aquatic environment (chronic) - category 4

Octamethylcyclotetrasiloxane is a SWA Class 3 Reproductive risk.

### **Potential Health Effects**

## Inhalation:

**Short Term Exposure:** Available data indicates that this product is not harmful. However product is believed to be mildly irritating, but unlikely to cause anything more than mild discomfort.

**Long Term Exposure:** No data for health effects associated with long term inhalation.

### **Skin Contact:**

**Short Term Exposure:** This product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but if treated promptly, all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

## **Eye Contact:**

**Short Term Exposure:** This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

Issued by: Sealants Australasia Pty Ltd Product: SA CONTRACTORS SILICONE

Page 4 of 5

Phone 08 9456 3627 (Business Hours) This version issued: August, 2016



Page 5 of 5

## Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

# **Carcinogen Status:**

**SWA:** No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

# **Section 12 - Ecological Information**

This product is not readily biodegradable. However, likely to degrade slowly in the soil or water and not cause long term problems.

# **Section 13 - Disposal Considerations**

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

# **Section 14 - Transport Information**

**UN Number:** This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

# **Section 15 - Regulatory Information**

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

#### **Section 16 - Other Information**

This SDS contains only safety-related information. For other data see product literature.

#### **Acronyms:**

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> edition)

AICS
SWA
Safe Work Australia, formerly ASCC and NOHSC
CAS number
Chemical Abstracts Service Registry Number
International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

**UN Number** United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous

Chemicals - Code of Practice" (December 2011) Copyright © Kilford & Kilford Pty Ltd, August, 2016. http://www.kilford.com.au/ Phone (02)9251 4532

Issued by: Sealants Australasia Pty Ltd
Page 5 of 5
Phone 08 9456 3627 (Business Hours)
Product: SA CONTRACTORS SILICONE
This version issued: August, 2016