

AL-F Food Grade Grease

Quick Reference Guide



Overview

Our AL-F Food Grade Grease is a high performance, all-round lubricant widely used in the food & beverage industries. This versatile grease has been certified in accordance with NSF-H 2, LFGB Section 31 and Section 5.

AL-F is white in colour and able to be used in applications between -30°C and +120°C.

AL-F Food Grade Grease can be used on many different types of bearings, joints, levers, guides, spindles, shafts, gears and cables.



Equipment Compatibility Chart

Rolling Bearings	•
Sliding Bearings	•
Chains	
Joints	•
Levers	•
Sliding Guides	•
Linear Guide Systems	
Spindles	•
Spline Shafts	•
Camshafts	•
Springs	
Open Gears	•
Worm Gears	•
Cables	

Key Specifications

Colour	White
Consistency Assignment	NLGI Class 2
Composition	Lithium Soap / Mineral Oil
Worked Penetration	280 +15 1/10 mm
Density at +20°C	0.9 g/cm ³
Temperature Rating	-30°C to +120°C

AL-F Grease Standard Sizes.

The table below lists all our standard sizes of AL-F Food Grade Grease. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at swiftsupplies.com.au/al-f-food-grade-greases-range

Part Number	Container Size	Pack Type
SWM000384B01V0001	350gm	Container
SWM000384B01V0002	400gm	Cartridge
SWM000384B01V0003	1kg	Container
SWM000384B01V0004	5kg	Container
SWM000384B01V0005	25kg	Container