# Natural Rubber Insertion Sheet & Strip Quick Reference Guide



#### Overview

Natural Rubber Insertion is an outstanding, general-purpose grade of rubber known for being economical, easy to handle and tough. It's manufactured from natural rubber compound and is reinforced with cotton cloth to provide it with additional strength and resistance to tearing.

Natural Rubber Insertion is black in colour and has smooth surface finishes on both sides.

Used for a variety of applications including...

- Gaskets and Seals
- Skirts
- Lining
- Sealing Strips
- Rubber Curtains
- Protecting Surfaces from Abrasion
- Pads and Strips
- General Sheeting Applications



### **Key Specifications**

Temperature Resistance	0°C to 70°C
Colour	Black
Insertion	Cotton
Hardness	60 (±5) Shore A
Elongation at Break	300%
Specific Gravity	1.55
Tear Strength	12 N / mm

### By the Metres Sizes.

The table below lists all our standard sizes of Natural Rubber Insertion that are available by the metre. To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at <a href="mailto:swiftsupplies.com.au/natural-rubber-insertion/">swiftsupplies.com.au/natural-rubber-insertion/</a>

Thickness	1200mm Wide, By the Metre.
1.5mm	SWM000005B01V0001
3mm	SWM000005B01V0002
4.5mm	SWM000005B01V0003
6mm	SWM000005B01V0004
9mm	SWM000005B01V0005
12mm	SWM000005B01V0006

#### Custom Insertion Rubber Gaskets, Washers, Seals and Parts.

We are always happy to assist with your custom rubber insertion requirements.

We have a range of insertion rubber table gaskets listed online to suit many different common flange sizes (e.g. BS, ANSI). We are also pleased to offer custom sized gaskets, strips washers and more cut from this material. For more information on custom NRI components, please do contact us.



# Natural Rubber Insertion Sheet & Strip Quick Reference Guide



## Natural Rubber Insertion Sealing Strips.

The tables below list all our standard sizes of Insertion Rubber Strips. All are available by the metre with a maximum, continuous roll length of 10 metres (e.g. if you order 16 metres it will be supplied as 1 x 10mtr roll and 1 x 6mtr roll).

To quickly find any on our website, just search for the SWM part number listed. Alternatively, browse the full range at <a href="mailto:swiftsupplies.com.au/natural-insertion-rubber-strip-range">swiftsupplies.com.au/natural-insertion-rubber-strip-range</a>

Width	1.5mm Thick	3mm Thick
25mm	SWM000005P01V0001	SWM000005P01V0016
35mm	SWM000005P01V0002	SWM000005P01V0017
40mm	SWM000005P01V0003	SWM000005P01V0018
50mm	SWM000005P01V0004	SWM000005P01V0019
75mm	SWM000005P01V0005	SWM000005P01V0020
100mm	SWM000005P01V0006	SWM000005P01V0021
150mm	SWM000005P01V0007	SWM000005P01V0022
200mm	SWM000005P01V0008	SWM000005P01V0023
250mm	SWM000005P01V0009	SWM000005P01V0024
300mm	SWM000005P01V0010	SWM000005P01V0025
350mm	SWM000005P01V0011	SWM000005P01V0026
400mm	SWM000005P01V0012	SWM000005P01V0027
450mm	SWM000005P01V0013	SWM000005P01V0028
500mm	SWM000005P01V0014	SWM000005P01V0029
600mm	SWM000005P01V0015	SWM000005P01V0030

Width	4.5mm Thick	6mm Thick
25mm	SWM000005P01V0031	SWM000005P01V0046
35mm	SWM000005P01V0032	SWM000005P01V0047
40mm	SWM000005P01V0033	SWM000005P01V0048
50mm	SWM000005P01V0034	SWM000005P01V0049
75mm	SWM000005P01V0035	SWM000005P01V0050
100mm	SWM000005P01V0036	SWM000005P01V0051
150mm	SWM000005P01V0037	SWM000005P01V0052
200mm	SWM000005P01V0038	SWM000005P01V0053
250mm	SWM000005P01V0039	SWM000005P01V0054
300mm	SWM000005P01V0040	SWM000005P01V0055
350mm	SWM000005P01V0041	SWM000005P01V0056
400mm	SWM000005P01V0042	SWM000005P01V0057
450mm	SWM000005P01V0043	SWM000005P01V0058
500mm	SWM000005P01V0044	SWM000005P01V0059
600mm	SWM000005P01V0045	SWM000005P01V0060